

## •規格 Specifications

測試依據In accordance with	IEC 61643-21:2005				
額定電壓 Nominal voltage (Vdc)	Un	5	12	24	48
最大持續工作電壓 (Vdc/ac) Max. continuous operating voltage	Uc	6/5	15/12	28/24	60/48
C2額定放電電流 Nominal discharge current(8/20)	In	5kA			
C2最大放電電流 Total nominal Discharge Current ( 8/20 $\mu$ s )		10kA			
箝制電壓 Voltage protection level (V)	L-L@C2 (8/20 $\mu$ s)	<30	<45	<55	<190
	L-G@C2 (8/20 $\mu$ s)	<500	<500	<500	<500
	L-L@C3 (1KV/ $\mu$ s)	<24	<38	<48	<145
	L-G@C3 (1KV/ $\mu$ s)	<600	<600	<600	<600
額定電流Nominal Current (A)	IL	0.5A			
傳輸速率 Transmission Speed ( bps )		2Mbps			
信號衰減量; 信號輸出差損 Insertion loss ; between input / output		$\leq 0.5$ dB) ; < 0.1%			
串聯電阻(每線) Series impedance per line (Ohm)		2.2 Ohm			
保護方式 Protection line		One pair			
安裝方式 Mounting		35mm DIN-rail in accordance with EN 50022/DIN46277-3			
接線方式Type of Connection IN/OUT		screw/screw			
材質 Materiale		ABS 合成樹脂			
尺寸Dimensions (mm)		89 X 13 X 59			
操作溫度Operating temperature range		- 40 $^{\circ}$ C ~ + 80 $^{\circ}$ C			